

PRIMARY CORNER DESCRIPTION The Cor. of Secs. 27 & 28 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1777)

A Stone in place 20 x 16 ins., 8" above ground which I mark with cross (X) at exact cor. point with 3 notches on E. and 2 notches on S. faces for cor. to secs. 27 and 28, from which
A Fir 4" dia., bears N.78°W., 80 lks. dist. mkd. T22S R10W S28 & 27 BT.
A Cedar 16" dia., bears S.66°E., 30 lks. dist. mkd. T22S R10W S27 BT.
A Fir 36" dia., bears S.53°W., 200 lks. dist. mkd. T22S R10W S28 BT.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11435)

The cor. of secs. 27 and 28 only, on the S. bdy. of sec. 22; lat. 43°38'15" N., longitude 123°52'45" W., is a stone in place, 20x16x8 ins., mkd. and witnessed as described in the official record.

Survey by A.G. Terry and R. Coughlin - For: Al Peirce Co. - Feb. 1955-April 1956 (Filed June 25, 1959) - M 15-17

Iron Pipe.
BTs - 20" Fir, due South, 4.0 ft.
16" Fir S.73½°E., 9.7 ft.
4' x 5' rock bears N.36°W., 22.6 ft.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 30, 1967 - C.S. File 55/64 and M 35-48

Orig. 20" x 16" x 8" stone, found in place, X on top, 2 notches visible on SW. side and 3 notches on SE. side, from which a:
4" Fir bears N.78°W., 80 lks.; now 72", scribes S28 visible, BT face covered. Dist. 76.0 ft.
16" Cedar bears S.66°E., 30 lks.; now 20" x 6' stub, portions of scribes R10 W S27 remaining. Dist. 24.2 ft.
36" Fir bears S.53°W., 200 lks.; missing. Steep sidehill, possible slide.

Restored:
Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R10W S22 S28 S27 1967 RS 359", 34" in ground on South side of original stone, and from which a:
(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 411300

PRIMARY CORNER DESCRIPTION Sec. cor. for 27 & 28 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

72" Fir, orig., bears N.78°W., scribed RS 359.
19" Fir bears S.62°E., 12.2 ft. scribed T22S R10W S27 BT
29" Fir bears N.47°W., 25.3 ft. scribed T22S R10W S22 BT.
Set 4" x 4" x 72" white painted cedar post 0.5 ft. N.50°W. of
corner stone.
OSFD metal location poster on 19" Fir BT.
NOTE: A.G. Terry cor. bears N.87°54'23"E., 301.15 ft.