

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 431300

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 27 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1778)

A Hemlock 5" dia., which I mark ¼ S on N. side for ¼ sec. cor., from which
 An Alder 6" dia., bears N.45°E., 40 lks. dist. mkd. ¼ S BT
 An Alder 5" dia., bears S.76°E., 13 lks. dist. mkd. ¼ S BT

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Surveyed Dec. 12, 1967 - Filed March 1968 - C.S. File 55/64 and M 35-48

1/4 Corner reestablished. Set OSBF 1½" x 36" galv. iron pipe mound of rock.
 20" Fir S.56¼°E., 38.8 ft. (RS 359)
 50" Fir N.76½°W., 31.2 ft.
Yellow metal location poster on 4" Hemlock, N.51 3/4°W., 2.1 ft. White painted cedar post, S.65°E., 2.2 ft.
Spur ridge course West, bears 51 ft. South.