

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor for Sec 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1742)

Set a Maple post 5 ft. long, 5" dia., 20" in ground for the ¼ sec. cor. on S. bdy. of sec. 34, from which
A Maple 10" dia., bears S.88°E., 31 lks. dist.
A Maple 8" dia., bears N.30°W., 22 lks. dist.

GL0 survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1759)

(38.00 chs.)
A Post 4" sq., 24" above ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Maple 10" dia., bears S.88°E., 31 lks. dist. mkd. ¼ S BT
A Maple 8" dia., bears N.30°W., 22 lks. dist. mkd. ¼ S BT.
I destroy this cor. and at:
(40.00 chs. West)
Set a stone 20x16x12 ins., 16" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
A Maple 8" dia., bears S.20°E., 30 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears N.52°W., 50 lks. dist. mkd. ¼ S BT.

Fd. and used in GL0 survey by Walker in 1906, under Contract #763 (DCSO records, Vol. 7 Page 2744)

Survey by Arnold G. Gibson - D.L. McConnell transitman - For: Oregon State Board of Forestry - March 1962 - C.S. File 42/331-6

Original 20" x 16" x 12" stone, found in place, ¼ on N. face, from which
8" Maple bears S.20°E., 30 lks.; now missing, group of small maples growing in place.
10" Fir bears N.52°W., 50 lks.; now rotten stump.
Set 4"x4"x72" white painted cedar post 2.0 ft. SW of corner stone, from which
28" Fir bears N.25½°W., 39.6 ft. scribed ¼ S34 BT RS 359.
18" Fir bears N.46°E., 54.8 ft. scribed ¼ S34 BT.