

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1776)

-----

A bluff of sandstone 5 ft. high, 10 ft. long, which I marked with cross (X) at exact cor. point with  $\frac{1}{4}$  S. for  $\frac{1}{4}$  sec. cor., from which

A Fir 36" dia., bears N.64°E., 26 lks. dist. mkd.  $\frac{1}{4}$  S BT.

A Fir 4" dia., bears S.5°E., 6 lks. dist. mkd.  $\frac{1}{4}$  S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - March 7, 1958 - C.S. File 42/341

-----

Original sandstone bluff 5'x10', found in place, X $\frac{1}{4}$  S on SE. face, from which:

4" Fir bears S.5°E., 6 lks.; now missing.

36" Fir bears N.64°E., 26 lks.; now 49" snag, scribed  $\frac{1}{4}$  S visible on upper face.

Restored:

20" Fir bears S.28 $\frac{1}{2}$ °W., 19.6 ft. scribed  $\frac{1}{4}$  S34 BT.

24" Fir bears N.40°W., 23.3 ft. scribed  $\frac{1}{4}$  S27 BT RS359.

OSBF metal location poster on 20" Fir BT.