

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1792)

Set a sandstone 20x18x12 ins., 16" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 30" dia., bears N.82½°W., 130 lks. dist. mkd. ¼ S BT
A Fir 12" dia., bears S.71°W., 175 lks. dist. mkd. ¼ S BT.

Found 14" x 16" stone - 1934 OSHD survey - See County Surveyor file A-3

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #149, surveyed June 1936. - (DCSO records Vol. 27 Page(s) 11447)

The ¼ sec. cor. of secs. 15 and 22 is a sandstone 20x20x10 ins., firmly set, mkd. ¼ S on N. face, with a cross on top and no accessories.

At point for cor.

Set an Iron post 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap mkd:

	¼	S 15
		S 22
		1936

from which

A Fir 25" dia., bears N.36°45'W., 31 lks. dist. mkd. ¼ S15 BT.

A Fir 28" dia., bears S.38°30'E., 44 lks. dist. mkd. ¼ S22 BT.

Cor. Fd. 1955/56 by Terry & Coughlin - M 15-17

Cor. Fd. OK, Feb. 1960 by OSBF - C.S. File 42/341

Survey by Harvey Wilcox - For: Jerry Harris - August 1991 - M 113-76 A&B

Found - 2½" brass cap with orig. stone alongside.
43" Fir stump bears N.37°W., 20.5 ft., with healed face.
48" Fir stump bears S.38°E., 29.0 ft. w/healed face.

New Bearing Object:

Power pole No. 9E bears N.31°E., 81.3 ft.