

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1751)

An Alder 4" dia., which I marked $\frac{1}{4}$ S. on N. side for $\frac{1}{4}$ sec. cor., from which,

An Alder 4" dia., bears N.63°E., 10 lks. dist. mkd. $\frac{1}{4}$ S BT.

An Alder 6" dia., bears S.50°E., 28 lks. dist. mkd. $\frac{1}{4}$ S BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1042)

Intersect the point for old $\frac{1}{4}$ sec. corner, located by reference to the old bearing trees. At the exact cor. point set an iron post, 3 ft. long, 1" dia., 26" in the ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap mkd: $\frac{1}{4}$ _____

S 3
1919

from which,

A Cedar 48" dia., bears S.62°E., 49 lks. dist. mkd. $\frac{1}{4}$ S3 BT.

A Maple 12" dia., bears S.39°W., 87 lks. dist. mkd. $\frac{1}{4}$ S3 BT.