

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 478100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 3 only, T23-10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1742)

Set a Maple post, 5 ft. long, 5" dia., 20" in ground for the ¼ sec. cor. on N. bdy. of sec. 3, from which
A Fir 40" dia., bears S.65°W., 32 lks. dist.
A Fir 40" dia., bears N.25°W., 39 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1758)

At this point which is a rock on SW. slope, 6 ft. high, 20 ft. long.
A Fir 40" dia., bears S.65°W., 32 lks. dist. mkd. ¼ S BT.
A Fir 40" dia., bears N.25°W., 39 lks. dist. mkd. ¼ S BT.
The post being gone, I marked stone with cross (X) at exact cor. point with ¼ S on ¼ sec. cor. on N. bdy. sec. 3.

GLO survey by Levi C. Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 1848)

My line falls 59 lks. S. of the old ¼ sec. cor. established under Contract #292. I destroy all evidence of this ¼ sec. cor.