

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1770)

This point falling on a stone in place 3x5x4 ft. high, I mark with a cross (X) at exact cor. point for ¼ sec. cor. marked ¼ S. on W. face, from which

An Alder 6" dia., bears S.28°W., 30 lks. dist. mkd. ¼ S BT
A Fir 5" dia., bears S.75°W., 40 lks. dist. mkd. ¼ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14849-50)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4
S 34 S 35
T 22 S R 10 W
1970

from which

A Fir 22" dia., bears N.40°E., 53 lks. dist. mkd. ¼ S35 BT
A Fir 26" dia., bears N.79½°W., 13 lks. dist. mkd. ¼ S34 BT.

and a tree of no record

A Fir 23" dia., bears S.81°E., 24 lks. dist. with fragmentary scribe marks visible on partially opened blaze.