

|       |       |             |       |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page 1770)

-----

A Fir on line, 10" dia. which I marked T22S S26 on NE.; R10W S35 on SE.; S34 on SW.; S27 on NW with 1 notch on S. & 2 notches on E edges for cor to secs 26, 27, 34 & 35 from which

    An Alder 5" dia. bears N.85°E. 24 lks mkd T22S R10W S26 BT

    A Fir 10" dia., bears S.70°E., 8 lks. mkd T22S R10W S35 BT

    A Fir 12" dia., bears S.8°W., 35 lks. mkd T22S R10W S34 BT

    A Fir 12" dia., bears N.14°W., 68 lks mkd T22S R10W S27 BT

This cor. is on top of a narrow rocky spur. Mill Creek washes both sides. it is about 300 ft. above creek.

BLM resurvey by James E Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page 14850)

-----  
The Sec. cor., determined at record bearing and distance from the remains original bearing trees:

    A Fir 40" dia., bears S.70°E., 8 lks. with fragmentary scribe marks visible on partially open blaze.

    A Fir 40" dia., bears S.8°W., 35 lks. with healed blaze.

    A Fir 44" dia., bears N.14°W., 68 lks. with healed blaze. and a tree of no record

    A Fir 42' dia., bears N.76°E., 45 lks. with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

|   |          |    |   |          |    |
|---|----------|----|---|----------|----|
| T | 22       | S  | R | 10       | W  |
|   | <u>S</u> | 27 |   | <u>S</u> | 26 |
|   | S        | 34 |   | S        | 35 |
|   |          |    |   | 1970     |    |

from which a new bearing tree

    A Fir 14" dia., bears N.8°E., 54 lks. mkd T22S R10W S26 BT

BLM Dependent resurvey by Edith Forkner, Cadastral Surveyor, under Group #2750, surveyed April/May 2014 - (Plat T22-10-2016-1 all info on plat & DCSO records Vol. 58 Pgs 23319-20)

-----  
The cor. of secs. 26, 27, 34, & 35, monumented with an iron post, 2½" dia, firmly set, projecting 2" above ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees

    A fir, 50" dia, bears S.70°E., 5.3 ft., with no marks visible on partially healed blaze at breast height.

    A fir, 51" dia, bears S.8°W., 23.1 ft., with a healed blaze at breast height.

    A fir snag, 51" dia, bears N.9°W., 44.9 ft., with a healed blaze at breast height. (Record, N.14°W.) Cont. next pg

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

|       |       |             |       |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

and a bearing tree mkd. by person(s) unknown  
A fir, 58" dia, bears N.76°E., 29.7 ft., with a healed blaze at breast height.  
and a bearing tree mkd. by Jelley in 1970  
A fir, 19" dia, bears N.8°E., 35.6 ft., with a small healed blaze at breast height and a healed blaze at base with illegible scribe marks on the bark along the left side.  
There are no new bearing trees available in sec. 27 within limits. Drive an aluminum angle iron alongside the cor.