

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1772)

Set a sandstone 18x14x10 ins., 12" in the ground for ¼ sec. cor. mkd. ¼ S. on W. face, from which
An Alder 6" dia., bears S.2°W., 150 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears East, 68 lks. dist. mkd. ¼ S BT.

Survey by Arnold Gibson - Wit: P.Lewellyn; T.South; M.Pounds;
Dec. 14, 1962 - C.S. File 43/341

Original 18"x14"x10" sandstone, in place, ¼ S visible, from which a:
6" Alder bears S.2°W., 150 lks.; now missing.
30" Fir bears East, 68 lks.; now 46", scribes 4S visible.
Set 4"x4"x72" White painted cedar post 1.0 ft. NW. of corner stone, from which
36" Fir bears N.6°W., 49.9 ft., scribed ¼ S27 RS359.
OSBFD metal location poster on 36" Fir BT.

Fd. OK, Dec. 1967 by A. Gibson - M 35-48