

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1790)

-----

Marked a stone in place 5x5x4 ft. high with cross (X) at exact cor. point and ¼ S. on W. side, for ¼ sec. cor., from which

- A Maple 36" dia., bears N.9°W., 64 lks. dist. mkd. ¼ S BT
- A Maple 10" dia., bears N.20°E., 56 lks. dist. mkd. ¼ S BT

Fd. Cor., 1955/56 by Terry and Coughlin - M 15-17

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 12, 1967 - Filed March 1968 - C.S. File 55/64 and M 35-48

-----

Orig. 5'x5'x4' stone, in place, 4" X, ¼ S on W. side, from which a:

- 36" Maple bears N.9°W., 64 lks.; now missing.
- 10" Maple bears N.20°E., 56 lks.; now 30" Maple, rotted in center, orig. axe work in bark, (dist. 66 lks.)

Rewitnessed:

- 30" Maple, orig., bears N.20°E., 43.6 ft.
- 48" Fir bears S.60°E., 64.2 ft., scribed ¼ S23 BT.
- 31" Maple, one of clump of three, bears S.49°W., 57.7 ft. scribed S22 BT RS 359.

OSBF metal location poster on 31" Maple BT S.49°W.