

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1788-89)

Set a sandstone 16x12x6 ins., 12" in the ground for cor. to secs. 14, 15, 22 and 23, marked with 3 notches on S. and 2 notches on E. edges and raised a mound of stone 2 ft. high, 3 ft. base, from which

- A Fir 4" dia., bears N.30°E., 50 lks. dist. mkd. T22S R10W S14 BT.
- A Fir 4" dia., bears S.12°E., 15 lks. dist. mkd. T22S R10W S23 BT.
- A Fir 4" dia., bears S.45°W., 20 lks. dist. mkd. T22S R10W S22 BT.
- A Fir 20" dia., bears N.68°W., 75 lks. dist. mkd. T22S R10W S15 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Feb. 1960 - C.S. File 42/341

Original sandstone 16"x12"x6" in ground in mound of stone, now missing, point on top edge 40 ft. bluff.

- 4" Fir bears N.30°E., 50 lks.; now 11", face grown over, found to be 50 ft. instead of 50 lks.
- 4" Fir bears S.12°E., 15 lks.; now 11", face grown over.
- 4" Fir bears S.45°W., 20 lks.; now 12", exposed scribe R found to be 20 ft. dist. instead of 20 lks.
- 20" Fir bears N.68°W., 75 lks.; now 36" windfall, face grown over, found stump hole to be 75 ft. dist. not 75 lks.

Set 1½" x 36" galv. I.P. with 3" bronze cap mkd: "Ore. St. Bd. of Forestry T22S R10W S14 S15 S22 S23 1960 RS 359", 24" in ground, in mound of stone, and from which a:

- 11" Fir bears N.81½°W., 34.5 ft., scribed T22S R10W S15 BT RS359.

OSBF metal location poster on orig. 4" Fir BT S.45°W.
Set 4" x 4" x 72" white painted cedar post 1.8 ft. NE of pipe.

Fd. OK, July 1989 by R. Stuntzner - M 108-41
Fd. OK, Aug. 1991 by H. Wilcox - M 113-76 A&B