

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1813)

-----

On E. point of a divide. Where it turns northward, I set a post 4 ft. long, 4" sq., for ¼ sec. cor. mkd. ¼ S. on W. face, from which

A Fir 8" dia., bears S.87°E., 5 lks. dist. mkd. ¼ S BT.

A Fir 4" dia., bears N.82°W., 10 lks. dist. mkd. ¼ S BT.

Ernesto Alvarado - U.S. Forest Service - Crew: Carol Dickinson; Colin Long - April 4, 1982 - C.S. File 61/32-2

-----

Found - Orig. 15" D.Fir now 5 ft. high snag bears S.88°E., 3.3 ft. Chopped into healed face, found blaze 2.7 ft. long, 0.2 ft. wide with scribing ¼ S BT.

Set DCSO brass cap on 3/4" I.P., 36" long with flanged bottom mkd: "T22S R10W S10 S11 1/4 1982".

New BTs -22" D.Fir bears N.9°30'W., 7.6 ft. scribed ¼ S10 CS BT.

34" D.Fir bears S.75°30'W., 11.8 ft. scribed ¼ S10 CS BT.

Location: Go along Rd. #210 approx. 1.7 miles to second large clearcut (South of road). Take main ridge West. Walk ridge staying West and South. Follow ridge approx. 5000 ft. to corner, which lies on East side of ridge near top.