

PRIMARY CORNER DESCRIPTION N. Sec. cor. for 2 & 3 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1750-51)

An Alder 4" dia., on line which I marked S2 on E.; T22S R10W on S.; S3 on W., with 2 notches on E. and 4 notches on W. faces for cor. to secs. 2 & 3, from which,
 An Alder 3" dia., bears N.70°E., 6 lks. dist. mkd. T22S R10W S2 & 3 BT.
 An Alder 7" dia., bears S.70°E., 15 lks. dist. mkd. T22S R10W S2 BT.
 An Alder 5" dia., bears S.5°W., 20 lks. dist. mkd. T22S R10W S3 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1041)

Intersect the old cor. of Secs. 2 and 3, which is an Alder tree, mkd. and witnessed as described by the Surveyor General. Alongside the old cor., Set an iron post, 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 2 and 3, with brass cap marked:

 S3 S2
 T22S R10W
 1919

from which
 An Alder 7" dia., bears S.70°E., 15 lks. dist. mkd. T22S R10W S2 BT.
 An Alder 10" dia., bears S.5°W., 20 lks. dist. mkd. T22S R10W S3 BT.