

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 503500

PRIMARY CORNER DESCRIPTION Cor. for Secs. 10 and 11 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a sandstone 24x20x10 ins., 18" in the ground for cor. to secs. 10 and 11, marked with 2 notches on E. and 4 notches on S. edges, from which

A Fir 36" dia., bears N.5°E., 150 lks. dist. mkd. T22S R10W S11 BT.

A Fir 36" dia., bears S.84°E., 83 lks. dist. mkd. T22S R10W S10 and 11 BT.

A Fir 40" dia., bears N.72°W., 190 lks. dist. mkd. T22S R10W S10 BT.

Survey by Harvey Wilcox - For: Jerry Harris - August 1991
M 113-76 A&B

Found - Rotten Fir snag bears N.72°W., 121.1 ft. (Orig. 125.4 ft.)

Rotten Fir snag bears N.5°E., 84.1 ft. (Orig. 99.0 ft.)

Rotten Fir snag bears S.84°E., 52.5 ft. (Orig. 54.8 ft.)

Set 3/4" x 30" Iron rod with 2" alum. cap at original position.

New BTs -38" Fir bears N.86°W., 11.3 ft. scribed "T22S R10W S10 BT" with X and tag.

18" Alder bears N.25°E., 48.5 ft. scribed "T22S R10W S11 BT" with X and tag.