

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 & 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 292 survey dated Aug. 7, 1878 (DCSO records Vol. 4 Page(s) 1741)

-----

Set a Maple post 5 ft. long, 5" dia., 20" in the ground for the cor. to secs. 35 and 36, from which,  
A Fir 30" dia., bears N.85°E., 24 lks. dist.  
A Fir 60" dia., bears N.10°W., 42 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1756)

-----

(71.85 chs.)  
The established cor. to secs. 35 and 36. This distance being too short and the cor. not having been closed upon I destroy the cor. and at  
(73.45 chs.)  
Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 35 and 36, marked S36 on E.; T22S R10W on N.; S35 on W. with 1 notch on E. and 5 notches on W. faces, from which  
A Fir 36" dia., bears N.82°E., 175 lks. dist. mkd. T22S R10W S36 BT.  
A Fir 36" dia., bears S.82°W., 114 lks. dist. mkd. T22S R10W S35 & 36 BT.  
A Fir 36" dia., bears N.75°W., 52 lks. dist. mkd. T22S R10W S35 BT.

GLO survey by Levi C.Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 5 Page(s) 1849)

-----

(26.00 chs.)  
At this point, I make diligent search for the old cor. of secs. 35 and 36, established under Contract #292 but can find no trace of it.  
(31.55 chs.)  
Intersect the cor. of secs. 35 and 36, T22S R10W which is a post, firmly set, marked and witnessed as described by the Surveyor General.

Survey by Arnold Gibson and Elbert Driver, Wit: Dennis Bagger; Derald Timmons and Ron Witham, - For: Oregon State Board of Forestry - Feb. 24, 1958 - C.S. File 42/341

-----

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 & 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Found - Orig. post, found rotted and down, scribing visible.  
36" Fir bears N.75°W., 52 lks.; now 54" stump,  
scribed 2 S35 visible, also, not orig., scribed  
T22S R10W BT and portion of 35 visible on down  
log.  
36" Fir bears S.82°W., 114 lks.; now 63" stump, face  
unexposed.  
36" Fir bears N.82°E., 175 lks.; now 56" uproot  
snag, face unexposed.  
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St.  
Bd. of Forestry T22S R10W S35 S36 T23S R10W S2 1958 RS 359",  
33" in ground, and from which a:  
19" Hemlock bears N.45°E., 8.0 ft. scribed T22S R10W  
S36 BT.  
20" Hemlock bears N.87°W., 40.2 ft. scribed T22S  
R10W S35 BT RS 359.  
OSBF metal location poster on 19" Hemlock BT.

Fd. and Used in BLM resurvey by James Jelley, under Group  
#718, surveyed June/Aug. 1970 - (DCSO records, Vol. 36 Page  
14838)

Survey by Daniel W. Baker - For: International Paper Co. -  
April 1987 - C.S. File 63/50-6 and M 104-19

-----  
Found - OSBF brass cap 1958.  
A 33" Hemlock bears N.44°E., 9.0 ft. (OSBF)  
60" Fir stump bears S.75°W., 76.0 ft. (1894)  
54" Fir stump bears N.75°W., 34.5 ft. (1894)  
16" Hemlock bears N.66°W., 33.0 ft. (1970 BLM BT.)  
(Not of record.)