

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1769)

A Maple 10" dia., which I mark for ¼ sec. cor. marked ¼ S on W. face, from which
A Maple 8" dia., bears N.69°W., 36 lks. dist. mkd. ¼ S BT.
A Maple 8" dia., bears S.20°E., 45 lks. dist. mkd. ¼ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14844)

Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap marked:

1/4
S 35 S 36
T 22 S R 10 W
1970

from which

A Fir 10" dia., bears S.82 3/4°E., 92 lks. dist. mkd. ¼ S36 BT.

A Fir 5" dia., bears N.17½°W., 68½ lks. dist. mkd. ¼ S35 BT.