

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 274 survey dated Sept 10, 1877 (DCSO records Vol 4 Page 1737)

Set stone 2x16x30 And made stone mound for ¼ sec cor. No trees near.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page 1774)

I made diligent search for ¼ sec. cor. but failed to find any. I therefore set temp. ¼ sc. cor.

I again make diligent search for ¼ sec. cor. and failing to find any, I therefore marked a Maple on line, 4" dia., ¼ S. on W. face for ¼ sec. cor., from which

A Maple 4" dia., bears S.60°E., 2 lks. dist. mkd. ¼ S BT.

A Maple 4" dia., bears S.18°W., 2 lks. dist. mkd. ¼ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14847)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Seat a brass tablet 3¼" dia., 3½" stem, in drill hole in solid rock, with top mkd:

1/4
S 26 | S 25
T 22 S | R 10 W
1970

from which

A Fir 14" dia., bears S.40°E., 17 lks. dist. mkd. ¼ S25 BT

A Yew 8" dia., bears S.71°W., 17 lks. dist. mkd. ¼ S26 BT.

BLM Dependent resurvey by Edith Forkner, Cadastral Surveyor, under Group #2750, surveyed April/May 2014 - (Plat T22-10-2016-1 all info on plat & DCSO records Vol. 58 Pgs 23319-20)

The ¼ sec. cor. of secs. 25 & 26, monumented with a brass tablet, 3¼" dia, firmly set in a nearly vertical rock face, with top (properly) mkd.

from which the remains of the BTs mkd. by Jelley in 1970

A decayed fir stump, size indeterminate, bears S.33¼°E., 12.3 ft., no marks visible. (Record, S.40°E., 11.2 ft.)

A yew, 9" dia, bears S.64½°W., 11.2 ft with scribe marks ¼ & other illegible scribe marks visible on partially healed blaze. (Record, S.71°W.)

and a new bearing tree

A pistol-butt hemlock, 11" dia, bears S.46½°E., 26.5 ft., mkd. ¼ S25 BT.

Drive an aluminum angle iron 15 ft. S. of the cor.