

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 274 survey dated Sept. 10, 1877 (DCSO records Vol. 4 Page(s) 1737)

Set stone 3x14x28 for the cor. to secs. 23, 24, 25 and 26, from which

A Fir 6" dia., bears N.88°E., 43 lks.

No other green timber near in secs. 23, 25 or 26.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1773)

Cor. to secs. 23, 24, 25 and 26, which is a stone 28x14x3 ins. set in the ground, from which

A Fir 6" dia., bears N.88°E., 43 lks. dist. mkd. T22S R10W S24 BT.

This cor. is on top of a bluff of sandstone 40 ft. high facing SW.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: P. Lewllyn, T. South, M Pounds - - Dec. 14, 1962; Apr. 26, 1965 - C.S. File 42/341

Found - Orig. stone 3"x14"x28" is missing.

6" Fir bears N.88°E., 43 lks.; now 22", face visible, no scribes.

Retracement by Todd in 1894, no other trees added. Steep South slope bears West, and line of orig. blazes. Divide bears South 660.0 lks.; in place. Foot of bluff bears South 15 lks.; in place. Original and retracement line blazes South.

Restored: Scribed X in bedrock on top of bluff, in mound of rock.

16" Fir bears N.40°W., 11.2 ft. scribed T22S R10W S23 BT.

16" Fir bears N.26½°E., 20.5 ft. scribed T22S R10W S24 BT.

22" Fir (orig.) bears N.88°E., 28.4 ft. scribed RS 359.

14" Fir bears S.61½°W., 3.0 ft. scribed T22S R10W S26 BT.

3' x 10' rock face bears S.66½°E., 6.9 ft. scribed X BO.

OSBFD metal location poster on 16" Fir BT, N.40°W.

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14847-48)

The sec. cor. perpetuated and recorded by the OSBF in 1962, monumented with a mound of stone, 3 ft. base, 2 ft. high, mkd. X on bedrock at base, from which the remaining original bearing tree:

A Fir 22" dia., bears N.88°E., 43 lks. dist. with fragmentary scribe marks visible on partially opened blaze.

and bearing trees mkd. by the OSBF:

A Fir 17" dia., bears N.26¼°E., 30½ lks. dist. with fragmentary scribe marks visible on partially open blaze.

A Fir 15" dia., bears S.62½°W., 4½ lks. dist. with fragmentary scribe marks visible on partially open blaze.

A Fir 15" dia., bears N.43°W., 16 lks. dist. with fragmentary scribe marks visible on partially open blaze.

At the corner point

Set a brass tablet ¾" dia., ½" stem, in drill hole, in solid rock, with top mkd:

T 22 S R 10 W
S 23 S 24
S 26 S 25
1970

Fd. brass cap in bedrock and accessories of record, June 1983, by E. Wobbe - M 94-51