

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600337

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 23 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1832)

A Hemlock 6" dia., which I mark with $\frac{1}{4}$ S. on W. side for $\frac{1}{4}$ sec. cor., from which

A Hemlock 6" dia., bears N.45°W., 11 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 6" dia., bears S.30°E., 30 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Oct. 27, 1969 - M 38-59

Set OSBF 1 $\frac{1}{2}$ " x 36" I.Pipe with 3" brass cap.

24" Hemlock S.12 3/4°E., 36.0ft. (RS 359)

45" Fir N.82 $\frac{1}{2}$ °W., 35.6 ft., yellow metal poster.

White painted cedar post, 4x4x72", NE. 1.3 ft.

Survey by Lloyd D. Smith - Wit: James McIntosh - For: Oregon State Board of Forestry - Sept. 13, 1983 - C.S. File 58/164-6

Found - A reestablished corner by Gibson in 1969, a 1 $\frac{1}{2}$ " x 36" galv. I.P., 34" in ground, from which

24" Hemlock bears S.12 3/4°E., 36.0 ft.; now 25" in place, I obliterate face.

45" Fir bears N.82 $\frac{1}{2}$ °W., 35.6 ft.; now 47" in place, face closed.

Remarked 1 $\frac{1}{2}$ " x 36" galv. I.P. with 3" bronze cap "OREGON STATE BOARD OF FORESTRY T22S R10W 1/4 S23 1983 LS1101"

New BT - 33" Fir bears S.42 $\frac{1}{2}$ °W., 31.3 ft. to face; scribed $\frac{1}{4}$ S23 BT.

A 4" x 4" x 72" white painted cedar post (1969), NE 1.3 ft. from corner pipe. OSFD metal location poster on 47" Fir (1969) N.82 $\frac{1}{2}$ °W., 35.6 ft.