

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1807)

Set a stone 24x16x10 ins., 18" in the ground for cor. to secs. 11, 12, 13 and 14, marked with 4 notches on S. and 1 on E. edges, from which

A Fir 44" dia., bears N.83°E., 87 lks. dist. mkd. T22S R10W S12 BT.

A Fir 40" dia., bears S.80°E., 87 lks. dist. mkd. T22S R10W S13 BT.

A Fir 40" dia., bears S.12°W., 15 lks. dist. mkd. T22S R10W S14 BT.

A Fir 40" dia., bears N.21°W.,, 70 lks. dist. mkd. T22S R10W S11 BT.

Survey by Harvey Wilcox - For: Jerry Harris - Aug. 1991 - M 113-76 A&B

Found - Fir snag bears N.21°W., 46.2 ft. (Orig)

Fir snag bears S.80°E., 57.4 ft. (Orig)

Fir snag bears N.83°E., 57.4 ft. (Orig)

Set 3/4" x 30" Iron rod with alum. cap mkd. "Stuntzner Engineering T22S R10W S11 S12 S13 S14 1991 LS 2244"