

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1811)

Marked an Alder 4" dia. T22S S1 on NE.; R10W S12 on SE.; S11 on SW.; and S2 on NW. with 1 notch on E. and 5 notches on S. sides for cor. to secs. 1, 2, 11 and 12, from which

A Fir 4" dia., bears N.50°E., 10 lks. dist. mkd. T22S R10W S1 BT.

An Alder 6" dia., bears S.28°E., 11 lks. dist. mkd. T22S R10W S12 BT.

An Alder 4" dia., bears S.7°W., 10 lks. dist. mkd. T22S R10W S11 BT.

An Alder 6" dia., bears S.6°W., 15 lks. dist. mkd. T22S R10W S2 BT.

Ernesto Alvarado, U.S. Forest Service - Crew: Carol Dickinson; Colin Long - April 6, 1982 - C.S. File 61/32-1

Found 15" D.Fir stump, 1 ft. high with center rotten, bears N.50°E., 6.63 ft. The stump was cut about two years ago has remains of a small flat face with axe marks visible behind a partially rehealed face that was cut out. Counted 41 growth rings to face. The snag was over 73 years old and I also compared it with the found orig. 15" D.Fir BT for the W 1/4 of Sec. 11, which was set at the same time. After establishing the corner point, I ran a loop traverse between secs. 1 and 2 and also tied the sec. cor. to 35 & 36, T21S R10W so I could compare calls and distances with GLO notes (Rec. dist. 6177.6 ft., measured 6089.02 ft.) The GLO calls for two definite points from the North, one call for two creeks 52.8 ft. apart and another call 1029.6 ft. from the corner, "along W. slope and then along E. slope, divide course S.80°W.," those check good. On the South, it calls for a divide course NW. but the only divide is about 1000 ft. away, but we have a spur 140 ft. South of the corner (GLO call 82.5 ft.) Calls going West to the ¼ location fit reasonably well. I met on the ground with Douglas County re-monumentation crew and Harvey Wofford, Land Surveyor from BLM, Coos Bay, to evaluate all the evidence found; a comment by Harvey was that he would hold to the evidence over proportional measurement. 4/6/82 met with Douglas Co. 3/29/82 met with Wofford. (Statement letter attached to C.S. File notes.)

Set DCSO brass cap on 3/4" I.P., 36" long with flanged bottom. Cap is mkd: T22S R10W S2 S1 S11 S12 1982.

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -34" D.Fir stump bears N.68°W., 72.5 ft. scribed T22S R10W S2 CS BT with 120 penny nail driven into top center, stamped BO.

30" D.Fir stump bears S.30°W., 138.3 ft. scribed T22S R10W S11 CS BT with 120 penny nail driven into top center stamped BO.

31" D.Fir stump bears S.9°E., 176.8 ft. scribed T22S R10W S12 CS BT with 120 penny nail driven into top center stamped BO.

Location: Go along Rd. #210 approx. 1.4 miles. Corner area is ribboned and visible in large clearcut South of road. Location poster on Hemlock on North bank of road. From poster, corner lies South 625 ft. Distances are to center of stumps.