

PRIMARY CORNER DESCRIPTION North Sec. Cor. for 1 & 2 only

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1750)

 Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1 and 2 mkd. S1 on E.; T22S R10W on S.; S2 on W., with 1 notch on E. and 5 notches on W. faces, from which,
 A Fir 40" dia., bears N.50°E., 43 lks. dist. mkd. T22S R10W S1 & 2 BT.
 A Fir 3" dia., bears S.30°E., 45 lks. dist. mkd. T22S R10W S1 BT.
 A Cedar 30" dia., bears S.68°W., 30 lks. dist. mkd. T22S R10W S2 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1039)

 The point for old cor. of secs. 1 and 1, located by reference to the old bearing trees. At the exact cor. point, Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 1 and 2, with brass cap mkd:

S2	S1
T22S	R10W
1919	

from which,
 A Fir 12" dia., bears S.55°E., 24 lks. dist. mkd. T22S R10W S1 BT. (Old BT)
 A Cedar 30" dia., bears S.68°W., 30 lks. dist. mkd. T22S R10W S2 BT. (Old BT)

BLM remonumentation by Norman J. McDonald, Cadastral Surveyor, under Group #350, surveyed May 15, 1963 - (DCSO records Vol. 31 Page(s) 13133)

 The cor. of secs. 1 and 2 only, which is monumented with an iron post, 3 ft. long, 2" dia., badly rusted, leaning and protruding 18" above the ground, with 1919 brass cap. The bearing trees are gone.
 At the corner point
 Set an iron post, 30" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

S 2	S 1
T 22 S	R 10 W
1963	

from which a new bearing tree, (Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION North Sec. cor. for 1 and 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed Fir stump 26" dia., bears S.51½°W., 39 lks. dist.
mkd. T22S R10W S3 BT.
No other suitable bearing tree or bearing object available
Deposit old iron post alongside new iron post as a
memorial.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack
Heritage, V. Perron, crew - May 1968 - C.S. File 54/1-31

Found - 1963 Cadastral brass cap and BTs, as follows:
26" sawed Fir stump S.51½°W., 25.7 ft., scribe
visible.
1919 BTs down. 1919 brass cap gone.
Set 6 ft. steel fence post alongside brass cap.
New BTs -18" Alder S.72°E., 41.0 ft. mkd. T22S R10W S1 CSBT
16" Alder S.51°E., 36.1 ft. mkd. T22S R10W S1 CSBT
This cor. lies on very steep, NW. slope near NE. corner of
clear cut unit and approx. 100 ft. W. and 75 ft. South of
solid rock ravine, course NW.

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S.
File 65/105-10

Found - 1963 BLM brass cap from which:
New BTs- 10" Fir, marked "X", BT tag, bears; N.5°38'E., 23.3
ft to spike.
18" Alder, marked "X", BT tag, bears; S.59°05'W.,
40.0 ft to spike.
15" Hemlock, marked "X", BT tag, bears; N.51°38'W.,
38.6 ft to spike