

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 633100

PRIMARY CORNER DESCRIPTION No. sec. cor. for 1 & 2 only, T23-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 292 survey dated Aug. 7, 1878 (DCSO records Vol. 4 Page(s) 1741)

-----  
Set a Fir post 5 ft. long, 5" dia., 18" in ground for the cor. to secs. 1 and 2, from which  
A Fir 8" dia., bears S.25°E., 28 lks. dist.  
A Fir 24" dia., bears S.88°W., 46 lks. dist.

GL0 survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1756)

-----  
A post 4" sq., firmly set 2 ft. above ground for cor. to secs. 1 and 2 marked S1 on E.; T23S R10W on S.; S2 on W.; with 1 notch on E. and 5 notches on W. faces from which,  
A Fir 8" dia., S.25°E., 28 lks. mkd. T23S R10W S1 BT.  
A Fir 24" dia., bears S.88°W., 46 lks. dist. mkd. T23S R10W S2 BT.

GL0 survey by Levi C.Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2759)

-----  
Cor. of secs. 1 and 2, original cor. gone.  
Set a Fir post 3 ft. long 4" sq., 24" in the ground for cor. of secs. 1 and 2, marked T23S S1 on SE.; R10W S2 on SW. face, with 1 notch on E., and 5 notches on W. edge, witnessed as described by the Surveyor General.

Survey by Arnold Gibson and Elbert Driver - For: Oregon State Board of Forestry - Sept. 9, 1957 - C.S. File 42/331-2

-----  
Found - Orig. post, now missing, from which a  
8" Fir now 29", S.25°E., 28 lks., exposed portion of scribe "S", bearing is S.38°E.  
24" Fir bears S.88°W., 46 lks., now 40", bark scribed T23S R10W S3 BT visible.  
Retracement by Walker in 1906, Post found, rotted and down, scribe T23S R10W S1 & 2 visible.  
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd: "Ore.St.Bd.of Forestry T22S R10W S36 T23S R10W S1 S2 1957 RS359", 33" in ground and from which a:  
16" Fir bears S.44°W., 13.5 ft. scribed RS 359.  
40" Fir, orig., bears S.88°W., 30.4 ft. scribed "BT" in wood.  
OSBF metal location poster on 16" Fir BT.

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 633100

PRIMARY CORNER DESCRIPTION No. Sec. cor. for 1 & 2 only, T23-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cor. Fd. and Used in BLM resurvey by James Jelley, under Contract #718, surveyed June/Aug. 1970 - (DCSO records, Vol. 36 Pages 14838-39)

Fd. OK April 1987 by D. Baker - C.S. File 63/50 and M 104-19

Survey by James McIntosh- For: Oregon State Board of Forestry - 5/2007 - M153-7

-----  
Found - OR ST Board of Forestry 1½"x36" galvanized IP w. 3" bronze cap 1957 (in place)  
8" fir (1878) S.25°E., 28 lks (now 44", S.38°E, Face closed)  
24" fir (1878) S.88°W., 46 lks (now 47" in place, bark scribes visible)  
16" fir (1957) S.44°W., 13.5' Yellow metal location poster (now 23" in place, face closed, Yellow metal location poster)  
Alum post west 0.90' with International Paper tags.  
Rewitnessed  
Orange carsonite marker, CBM-250 labeled witness post, S.60°E., 2.50' to base  
Orange carsonite marker, CBM-250 labeled witness post, S.62°W., 3.50' to base