

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 274 survey dated Sept 10, 1877 (DCSO records Vol 4 Page 1737)

Set a Maple post, 40" dia., for the ¼ sec. cor., from which
A Fir 60" dia., bears S.15°E., 27 lks.
A Fir 24" dia., bears S.20°W., 56 lks.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14845-46)

The ¼ sec. cor., determined at record distance from the original bearing trees:

A Fir 64" dia., bears N.75°E., 27 lks. dist. with scribe marks 1/4 S BT visible on bark blaze. (Rec. S.15°E.)

A Fir 38" dia., bears S.66½°E., 56 lks. dist. with scribe marks 1/4 S BT visible on bark blaze. (Rec. S.20°W.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 10" in the ground, to bedrock, mkd. X, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

1/4 $\frac{S\ 25}{S\ 36}$
T 22 S R 10 W

from which a bearing object:

A sandstone boulder, 7x7x6 ft. high, bears N.34¼°W., 30 lks. dist. mkd. X BO.

There are no suitable trees available within limits.

Fd. OK, Sept. 1982 by E. Wobbe - M 93-14

PLEASE NOTE: This corner was determined to be the South ¼ cor. of sec. 25 only, per 1992 GIS computations by Fritz Ingram.

ALSO NOTE: In a 2014 dependent resurvey, BLM used their 1970 BC which shows the 1/4 Corner to be common (Secs. 25 & 36)

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2750, surveyed April/May 2014 - (Plat T22-10-2016-1 all info on plat & DCSO records Vol. 58 Page(s) 23319-20)

The ¼ sec. cor. of secs. 25 & 36, monumented with an iron post, 2½" dia., firmly set, projecting 7" above a mound of stone, 4 ft base, 1 ft. high, with a brass cap (properly) mkd from which the remains of the original BTs

A decayed fir stump, 56" dia., bears N.76°E., 17.8 ft., no marks visible.

continued next page

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 & 36

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

A decayed fir stump, 39" dia., bears S.66½°E., 37.0 ft.,
no marks visible.

and new accessories

A fir, 13" dia., bears N.53°E., 4.0 ft., mkd. ¼ S25 BT.

A sandstone boulder, 7x5x5 ft., bears S.41½°W., 23.8 ft.,
to a Mag Nail pounded flush with the surface in the
center of a chiseled X and BO above.

The bearing object mkd. by Jelley, in 1970, was recovered
with no marks visible.

Drive an aluminum angle iron alongside the cor.

NAD 1983 (2011)

Latitude 43°37'23.01"N.

Longitude 123°50'06.83"W.