

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1723)

Set Maple post for ¼ sec. cor. from which,
A Maple stub 60" dia., 10 ft. high, bears N.3°W., 54 lks.
A Fir 48" dia., bears S.16°E., 308 lks. dist.

Survey by James Byron, Deputy Co. Surveyor - For: County Park Dept. - Sept. 1961 - M 22-16 and C.S. File 52/86

~~Set Brass cap on high bank mkd. County Surveyor's Office 1962
S 13 T22S R10W, from which
S 24~~

~~A 10" Myrtle bears N.28°W., 49.0 ft. scribed S13 CS BT.~~

~~Set 7 ft. steel fence post at B.C.~~

1/24/2017 - added 12/14/2020

This position is not the ¼ corner, it was set 59.98 ft east of the ¼ corner.

Survey by Eugene Wobbe, LS #1093 - For: International Paper Co. - June 15, 1983 - M 94-51

Set 1" Iron pipe with brass cap mkd. ¼ S13 S24 T22S R10W.
New BTs -14" Alder S.81°W., 16.9 ft.
9" Alder N.28°E., 5.0 ft.

Fd. OK, July 1989, by R. Stunzner - M 108-41

Fd. Cap and BTs, Sept. 1991 by G. Solarz - M 114-11

Fd. Ok by M. Heimburger, Jan. 2005 M147-8

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Mike Koch - 1/24/2017 (Filed 1/28/2021) - C.S. 67/48-14

Found - A 1" (I.D.) iron pipe, firmly set, buried 12" below ground level, with a 2½" brass cap (properly) mkd
A witness corner by Byron in 1961 per M 22-16 set 60 feet east of the quarter corner on the high bank was searched for and no evidence was found.

BTs by Wobbe in 1983 -

A 18" dia. Alder snag bears S.79½°W., 16.9 ft. with a healed double blaze. (rec. S.81°W.)

A 19" dia. Alder bears N.28°E., 5.0 ft. with a healed double blaze.

Continued next page

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - A 43" Maple bears S.25°W., 45.6 ft. (not blazed, scribed or tagged since it is located in Scottsburg County park.)
A 3/4" iron rod by Byron in 1961, buried 3" below ground level bears S.89¼°E. 422.0 ft. (computed rec. per M 22-16 & M94-51 S.89°51'21"E., 423.0 ft)

Note - Compass declination 15¼°E.
All BTs have BT tags attached. All New BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown.
Corner falls on sloping river bank 10 ft. NE of the high bank of the Umpqua river at the northerly edge of the baseball/softball field near the back stop at Scottsburg County Park.