

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Pg 1749)

Set a Post 4 ft. long, 4" sq., 24" in the ground mkd. ¼ S. on N. face for ¼ sec. cor., from which,
A Fir 20" dia., bears N.33°E., 34 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears S.70°W., 130 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1038)

The old ¼ sec. cor., which is a decayed post, mkd. and witnessed as described by the Surveyor General. The old bearing trees are dead. Alongside the old cor., Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for the ¼ sec. cor. of sec. 1 only, with brass cap mkd:

¼ S1
1919

from which

A Fir 8" dia., bears S.11°E., 44 lks. dist. mkd. ¼ S1 BT.
(New BT)
A Fir 8" dia., bears S.35°W., 40 lks. dist. mkd. ¼ S1 BT.
(New BT)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - May 1968 - C.S. File 54/1-7

Found - 1919 GLO brass cap in place. Pipe badly rusted.
Orig. 8" now 22" Fir, alive, S.11°E., 29.0 ft., shows good scar.
Orig. 8" now 10" Fir, decayed remains of stump only, S.35°W., 26.4 ft., find partial old blaze and reverse scribe in stump.

Set Brass cap at cor. mkd: County Surveyors Office

T 21 S
T 22 S R10W ¼ S 1
1968

New BTs -18" D.Fir S.60°E., 25.8 ft. mkd. ¼ S1 CS BT.
14" Alder S.49°W., 18.1 ft. mkd. ¼ S1 CS BT.

Deposit old corner pipe and brass cap alongside. This corner lies on moderate S. slope approx. 348 ft. N.88°E. of S¼ Sec. 36, T21-10.

continued next page

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S.
File 65/105-10

Found - 1968 DCSO brass cap from which:
28" Fir, face evident, bears; S.60°E., 25.8 ft to
center.
20" Fir snag, face evident, BT tag, bears; S.11°E.,
29.0 ft to center.
New BTs- 11" Fir, marked "X", BT tag, bears; N.19°E., 22.3 ft
to spike.
20" Fir, marked "X", BT tag, bears; S.26°W., 35.7 ft
to spike.