

PRIMARY CORNER DESCRIPTION Sec. cor. for 13 & 24; 18 & 19, T22-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1723)

- 
- Set post cor. to secs. 13, 18, 19 and 24.
- A Fir 20" dia., bears N.10°E., 76 lks. dist.
  - A Fir 6" dia., bears S.75°E., 33 lks. dist.
  - A Fir 14" dia., bears S.52°W., 5 lks. dist.
  - A Fir 24" dia., bears N.5°W., 12 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1767)

- 
- At the sec. point, A Fir 30" dia., mkd. T22S R9W S18 BT bears N.10°E., 76 lks. dist. The marks were made in the bark and badly defaced by decay and all other marks at this cor. had been destroyed by a slide. I therefore remarked this tree and reestablished the cor. as follows:
- Set a sandstone 14x12x8 ins., 10" in the ground for cor. to secs. 13, 24, 18 and 19, marked with 3 notches on N. and S. edges, from which
- Said Fir 30" dia., bears N.10°E., 76 lks. dist. mkd. T22S R9W S18 BT.
  - A Fir 16" dia., bears S.12°E., 66 lks. dist. mkd. T22S R9W S19 BT.
  - A Fir 12" dia., bears S.30°W., 40 lks. dist. mkd. T22S R10W S24 BT.
  - A Maple 12" dia., bears N.33°W., 84 lks. dist. mkd. T22S R10W S13 BT.

Survey by Wilford N. Haines - For: Charles Meade - Surveyed Nov. 12, 1958, filed Jan. 15, 1959 - M 13-63

-----

Found - Original corner and all BTs are standing.  
Drove 1" x 1" x 36" Iron rod in ground.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14843)

-----

The Sec. cor., monumented with the original sandstone, 14 x 12 x 8 ins. loosely set, on top of the ground, mkd. X on top, alongside of which is set a 3/4" T Iron, firmly set, projecting 8" above ground; from which the remaining original bearing tree:

(Cont. Next Page)

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. cor. for 13 & 24; 18 & 19, T22-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 50" dia., bears N.12½°E., 76 lks. dist., with scribe marks S R9W visible on partially open blaze. (Rec. N.10°E.)

and bearing trees by Todd in 1894:

A root hole bears S.12°E., 66 lks. dist. with a down Fir alongside, 22" dia., with fragmentary scribe marks visible on partially open blaze.

A Fir 26" dia., bears S.30°W., 40 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S  
R 10 W R 9 W  
S 13 S 18  
S 24 S 19  
1970

from which new bearing trees

A Fir 14" dia., bears S.69°E., 41 lks. dist. mkd. T22S R9W S19 BT.

A Fir 15" dia., bears N.67½°W., 29 lks. dist. mkd. T22S R10W S13 BT.

Deposit the original stone, and reset the T iron alongside the iron post.

Fd. OK, June 1983 by E. Wobbe - M 94-51