

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 12 & 13 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1746)

-----  
Set a sandstone 18x12x10 ins., 12" in the ground, marked with 4 notches on S. and 2 notches on N. edges for cor. to secs. 12, 13, 7 and 18, from which  
A Fir 6" dia., bears N.55°E., 5 lks. dist. mkd. T22S R9W S7 BT.  
A Fir 36" dia., bears S.71°E., 56 lks. dist., mkd. T22S R9W S18 BT.  
A Fir 30" dia., bears S.25°W., 35 lks. dist. mkd. T22S R10W S13 BT.  
A Fir 60" dia., bears N.38°W., 17 lks. dist., mkd. T22S R10W S12 BT.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1675)

-----  
Intersected West bdy. of T., 193 lks. North of the corner to secs. 12 and 13, T22S R10W, which is a stone 14 x 14 x 8 ins. above ground on steep hillside sloping SW., marked with 4 notches on the S., and 2 notches on the N. sides with X on top of stone, from which,  
A Fir 6" dia., bears N.40°E., 48 lks dist. mkd. T22S R9W S7 BT.  
A Fir 28" dia., bears S.63°30'E., 60 lks. dist. mkd. T22S R9W S18 BT.  
A Fir 30" dia., bears S.25°30'W., 40 lks. dist. mkd. T22S R10W S13 BT.  
A Fir 48" dia., bears N.40°W., 22 lks. dist. mkd. T22S R10W S12 BT.  
I destroyed mark on the East.

Survey by Eugene M. Wobbe, LS #1039 - For: International Paper Co. - Feb. 23, 1983 - M 90-41

-----  
Found - 50" Fir bears S.22°45'W., 25.6 ft. (opened to scribing)  
48" stump bears S.61°40'E., 38.6 ft.  
48" snag bears N.40°30'W., 13.5 ft.  
Set I.P. with brass cap mkd: S12 and 13 T22S R10W.

Fd. Ok - C. Mulkins - Oct. 31, 1995 - M 123-24

continued next page

TOWNSHIP 22 RANGE 10 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 12 & 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jerry Estabrook - For: Roseburg Resources - 7/2020 - M177-35

-----

Found - A 1½" iron pipe with 2 1/2" brass cap marked T22S  
R10W 12 13 R9W 18 1982" per M90-41.

A 14" rotten fir stump with axe marks on face bears  
N.40°E., 31.68'.

A 48" Fir stump with no visible marks bears  
S.61°40'E., 38.6'.

A 55" Fir with healed face and tag bears S.22'°5'W.,  
25.6'.

A 24" Fir with healed face and tag bears N.61°W.,  
23.5' Unknown record.

A 38" Fir snag with no visible marks bears  
N.40°30'W., 13.5'.

New BT - A 25" Fir, face scribed "SE S12 BT" with X-chop and  
tag bears S.67°E., 11.70' to a spike at side  
center.

LAT. And LONG. Per GARMIN ETREX hand held GPS:

N: 43°39'52.0" W: 123°49'37.3"