

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1680)

I set sandstone 18 x 16 x 8 ins., 12" in ground on hillside sloping E. at the point of intersection for closing corner to secs. 6 and 7, marked C.C. on the E. with 5 notches on the S. and 1 notch on the N. faces, from which

- A Fir 50" dia., bears N.48°E., 118 lks. dist. mkd. T22S R9W S6 BT.
- A Fir 6" dia., S.50°E., 43 lks. dist. mkd. T22S R9W S7 BT.
- A Hemlock 12" dia., bears S.68°W., 56 lks. dist. mkd. C.C. T22S R9W S6-7 BT.

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17943)

(90.56 chs.)

The closing cor. of secs. 6 and 7, monumented with the original sandstone, 18 x 25 x 7 ins., firmly set, 6" in the ground, mkd. CC on the E.; 1 notch on the N.; and 5 notches on the S. edges, from which the remains of the original bearing trees:

- A Fir snag 68" dia., bears N.48°E., 118 lks. dist. with healed blaze.
- A decayed Fir stump, size indeterminate, bears S.50°E., 42 lks. dist., no marks remaining. (Rec. 43 lks.)
- A root hole bears S.68°W., 56 lks. dist. with a downed Hemlock 30" dia., alongside with healed blaze.

Add the marks AM to the top of the stone and bury in place.

(90.00 chs.) (N.89°38'W)

Intersect the E. bdy. of sec. 1, T22S R10W.
 True point for the closing cor. of secs. 6 and 7.
 Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S	T 22 S
S 1	S 6 CC
	S 7
R 10 W	R 9 W
	1983

from which

- A Hemlock 23" dia., bears N.44½°E., 69 lks. dist. mkd. T22S R9W S6 CC BT.
- A Fir 90" dia., bears S.41°E., 58 lks. dist. mkd. T22S R9W S7 CC BT.