

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1877)

Intersect S. bdy. of Tp. at a point 4.80 chs. W. of the cor. of Tps. 23 S., Rs. 11 and 12 W. at which point, I SET a stone 24x12x6 ins., 16" in the ground for closing cor. to Tps. 22 S., Rs. 11 and 12 W., marked with 6 notches on the N.; E.; and W. sides, from which
A dead Cedar 20" dia., bears N.54°E., 18 lks. dist. mkd. T22S R11W S31 BT.
A Cedar stub 24" dia., bears N.85½°W., 118 lks. dist. mkd. T22S R12W S36 BT.
A Fir stub 36" dia., bears S.71°E., 69 lks. dist. mkd. C C T22S R11 & 12 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Nov. 1958 - C.S. File 42/403-5

Original stone 24" x 12" x 6", found in place with 6 notches on the North, from which a:
20" dead Cedar bears N.54°E., 18 lks.; now 16" burnt and rotted uproot, faint scribe marks visible.
24" Cedar stub bears N.85½°W., 118 lks.; now missing.
36" Fir stub bears S.71°E., 69 lks ; now rotted and burnt uproot.
Built mound of stone around original stone, from which a:
25" Fir bears N.17°E., 19.4 ft.; scribed T22S R11W S31 CC BT.
29" Fir bears N.30°W., 103.6 ft.; scribed T22S R12W S36 CC BT.
31" Fir bears S.20°E., 25.8 ft.; scribed RS 359.
OSBF metal location poster on 25" Fir BT.
Set 4 x 4 x 72" White painted Cedar post 1.0 ft. SE of stone.

Lloyd D. Smith - For: Oregon Dept. of Forestry - Dec. 22, 1982 - C.S. File 58/164-5

Found - 24" x 12" x 6" stone, lying face down, notches on North face badly eroded.
Three orig. trees described by Gibson in 1958 now missing.
Mound of stones by Gibson now scattered.
25" Fir now 28" x 4 ft. high stub in place, badly decayed scribes 22S R11W S31 visible, bears N.17°E., 19.4 ft.
29" Fir now 32" windfall 5 ft. downhill, face closed (Rec. N.30°W., 103.6 ft.)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp. Cor)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

31" Fir now 31" windfall, face closed. (Rec. S.20°E., 25.8 ft.)
Set 1½" x 36" alum. pipe with 3 ¾" alum. cap mkd. "State of Oregon Department of Forestry T22S R11W R12W CC S36 S31 T23S R12W S1 1982 LS1101", 34" in ground, placed orig. 24"x12"x6" stone alongside, and from which
New BTs -25" Cedar bears N.13°W., 36.8 ft. to face; scribed T22S R12W S36 CC BT.
9" Cherry bears N.80°E., 59.7 ft. to face; scribed T22S R11W S31 CC BT.
Set 4" x 4" x 72" white painted Cedar post S.49°W., 2.4 ft. from corner pipe. OSFD metal location poster on 25" Cedar N.13°W., 36.8 ft.

Survey by Lloyd D. Smith - For: State of Oregon Dept. of Forestry - Dec. 30, 1986 - M 103-42

Set Oregon State Dept. of Forestry 1¼" X 36" alum. pipe with 3 ¾" alum. cap and magnetic insert, 34" in ground.
New BTs -31" Fir N.08°W., 79.2 ft. scribed T22S R12W S36 CC BT with bearing tree tag.
27" Cedar N.25°W., 17.3 ft. to nail in base of face (OSDF 1982 NW BT) and bearing tree tag.
OSDF pipe and cap, S.0°10'02"W, 20.97 ft. stamped AM.
4"x4"x72" white painted Cedar post N.69°E., 1.2 ft.
Original closing cornr bears S.0°10'02"W., 20.97 ft.

Fd. OK, Feb. 1992 by Harvey Wilcox - M 114-75