

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION C C for Secs. 30 and 31 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1970)

-----  
I set a stone 18x12x8 ins., 12" in the ground for closing cor. to secs. 30 and 31, marked C.C. with 1 notch on S. and 5 notches on N. edges, from which  
A Fir stub 36" dia., bears N.65°E., 45 lks. dist. mkd. T22S R11W S30 BT.  
A Fir stub 40" dia., bears S.45°E., 192 lks. dist. mkd. T22S R11W S31 BT.  
A burnt Fir 36" dia., bears S.43°W., 193 lks. dist. mkd. T22S R11W CC S30 & 31 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - June 17, 1974 - C.S. File 57/4 -4

-----  
Found orig. 18x12x8" stone, in place, 5 notches on N. side, from which a:  
36" Fir stub bears N.65°E., 45 lks.; now 20" x 24" high stub, in place, burnt and badly decayed, no scribes visible.  
40" Fir stub bears S.45°E., 192 lks.; missing, in new slide out draw.  
36" burnt Fir bears S.43°W., 193 lks.; missing.  
Spur ridge bears East, 131 lks.; in place.  
Rewitnessed:  
45" Fir bears N.67°E., 5.3 ft. to face, scribed T22S R11W S30 CC BT.  
27" Fir bears S.48°E., 49.1 ft. to face; scribed T22S R11W S31 CC BT RS 359.  
Set 4"x4"x72" white painted cedar post 2.8 ft. N.33°W. of corner stone.  
OSBF metal location poster on 20" Fir, North 20.0 ft.