

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100227

PRIMARY CORNER DESCRIPTION C C for Secs. 25 and 36 only, T22-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2109-10)

At point of intersection (104 lks. S. of old Sec. cor.) I set a Fir post, 3 ft. long, 12" sq., 24" in the ground for closing cor. of secs. 25 and 36 mkd. CC T22S R12W on W.; S36 on S.; and S25 on N. face, with 1 groove on S. and 5 grooves on N. face, from which

A Willow 6" dia., bears S.47°W., 40 lks. dist. mkd. T22S R12W S36 BT.

A Maple 10" dia., bears N.42°W., 22 lks. dist. mkd. T22S R12W S25 BT.

Survey by Warren Hootman - For: Cape Arago Lumber Co. - Nov. 20, 1959 - C.S. File 51/62

Set a 4" Post and marked trees as follows:

Maple 18" DBH, bears N.53°E., 20.7 ft.

Chittum 12" DBH, bears S.75°W., 10.2 ft.

Myrtle 28" DBH, bears N.47°W., 31.1 ft.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - April 1975 - M 55-73

Set 1½" x 10" OSBF pipe and cap 10" in concrete, from which 11" Myrtle S.32°W., 45.3 ft.

36" Fir N.79°W., 124.2 ft. "RS 359", with yellow metal location poster.

White painted cedar post, S.70°W., 17.9 ft.