

PRIMARY CORNER DESCRIPTION Angle Point on W. bdy. Sec. 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1875)

Set a stone 12x9x8 ins., 8" in ground for cor. to secs. 25 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which
A Maple 10" dia., bears N.43°W., 29 lks. dist. mkd. T22S R12W S25 BT.
A Maple 8" dia., bears S.48°W., 41 lks. dist. mkd. T22S R12W S36 BT.
An Alder 14" dia., bears S.26°W., 20 lks. dist. mkd. T23S R12W S25 & 36 BT.

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2109)

The old cor. of secs. 25 and 36, which is a stone, marked and witnessed as described by the Surveyor General. I cut out the markings on this cor. and make an angle point of it as follows:
A sandstone 20x10x5 ins., 15" in the ground for Angle Corner marked A P on face, from which
A Maple 8" dia., bears S.48°W., 41 lks. dist. mkd. AP BT.
A Maple 10" dia., bears N.43°W., 29 lks. dist. mkd. AP BT

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Restored by Wm. E. Metcalf - June 18, 1974 - C.S. File 57/4-2

Found orig. 20x10x5" sandstone, found in place, outer surface decomposed, P remaining, from which a:
8" Maple bears S.48°W., 41 lks.; now 19", in place, exposed scribe T.
10" Maple bears N.43°W., 29 lks.; now 18" in place, face rotted out.
Hootman's closing cor. 25 & 36, bears South 104 lks.; in place.
Remarked original 20"x10"x5" sandstone with AP, from which a:
27" Myrtle bears S.83°W., 52.3 ft. to face; scribed AP S25 BT RS359.
37" Fir bears N.8°W., 79.3 ft. to face; scribed AP S25 BT.
Set 4"x4"x72" white painted cedar post 5.7 ft., N.12°W. of cornerstone.
OSFD metal location poster on orig. 19" Maple BT, S.48°W., 27.1 ft.