

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100327

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25, T22-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1874)

Set a post 4 ft. long, and 4" sq., 2 ft. in ground for cor. to secs. 24 and 25, marked T22S R12W on W.; S24 on N.; and S25 on S. sides, with 4 notches on N. and 2 notches on S. edges, from which
A Chittim 14" dia., bears S.61°W., 14 lks. dist. mkd. T22S R12W S25 BT.
A Hazel 5" dia., bears N.84°W., 5 lks. dist. mkd. T22S R12W S24 BT.
An Alder 20" dia., bears N.40°W., 22 lks. dist. mkd. T22S R12W S24 & 25 BT.

Tied and used in GL0 survey by Charles A. Slang, Deputy Surveyor under Contract #793, dated Feb. 17, 1910 (DCSO records, Vol. 5 Page 1978 (and duplicate page 2105)

Elliott State Forest Boundary Survey - L. Beyers and E. Lough 1939 or 1941 ? - (DCSO Field Book 123 Page 20)

Set a 4" x 4" cedar post 4 ft. long replacing post set by Whipple under Contract #612.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1960 - C.S. File 42/403-15

Original post, now missing, from which a:
14" Chittim bears S.61°W., 14 lks.; now missing.
5" Hazel bears N.84°W., 5 lks.; now 5", down and rotted, no scribes.
20" Alder bears N.40°W., 22 lks.; now 24", exposed portion of T and other scribes, bears N.40°E.
30" Fir line tree bears North 6.16 chs., found in place.
Ridge, course East, bears South 1.80 chs.; in place.
14" Fir line tree bears South 7.63 chs.; found in place.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Board of Forestry T22S R11W R12W S19 S24 S25 1960 RS359", 30" in ground and from which a:
45" Fir bears S.73°W., 15.3 ft. scribed T22S R12W S25 BT RS359.
27" Cedar bears N.56°W., 47.6 ft.; "T22S R12W S24 BT".
24" Orig. Alder BT, bears N.40°W., 14.5 ft.; scribed BT above orig. face.
Set 4"x4"x72" white painted cedar post 1.5 ft. SE of pipe.
OSBF metal location poster on 27" Cedar BT.

cont.

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100327

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T22-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - May 1991 - M 112-29

Found - OSBF 3" bronze cap dated 1960 on 1½" x 36" I.P. in place.
20" Alder, original, N.40°W., 22 lks.; now 24" N.50°E., 14.8 ft. to face.
45" Fir, 1960, S.73°W., 15.3 ft.; now 48" x 3 ft. high rotted stump, scribes visible, in place.
27" Cedar, 1960, N.56°W., 47.3 ft.; now 38" scribes visible in place.
White painted 4 x 4 cedar post, SE 1.5 ft. in place.
New Accessories:
24" Cedar S.82°W., 32.9 ft. scribed "T22S R12W S25 BT" and BT tag.
Orange carsonite marked S.71°W., 15.0 ft. to base, alongside 45" Fir BT.

Jerry Estabrook - For: Moore Mill & Lumber Co. - 5/2021 - M179-42

Found - A 3" bronze cap marked as shown and set on a 1½" iron pipe set per CS 42/403.
A 48" rotten stump w/carsonite post bears S.73°W., 15.3'.
A 38" Cedar w/visible scribe in healed face and tag bears S.82°W., 36.5', record 32.9' per M112-29.
A 48" Cedar w/healed face bears N.56°W., 48.4', record 47.6' per CS 42/403 and 47.3' per M112-29, a tag was added.
4X4 Cedar post bears N.90°E., 1.0', record SE 1.5' Per CS 42/403
New BTs- A 9" Hemlock, face scribed "SE S24 BT" with X-chop and tag bears N.66°W., 36.1' to a spike at side center.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS (not survey grade) N: 43°38'25.2" W: 124°03'50.4"