

PRIMARY CORNER DESCRIPTION A.P. on W. bdy. Sec. 19

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1873)</p> <p>-----</p> <p>Set a Post 3 ft. long, and 3" sq. for ¼ sec. cor. mkd. ¼S on W. face, from which A Fir 20" dia., bears N.¼°E., 29 lks. dist. mkd. ¼ S BT A Hemlock 24" dia., bears N.79°W., 49 lks. dist. mkd. ¼ S BT.</p>
<p>GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page 1979 (and a duplicate page, 2106))</p> <p>-----</p> <p>The old ¼ sec. cor. I destroy all trace of this old ¼ sec. cor. and reestablish it at the same point as follows: Set a sandstone 12x10x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face; from which Spruce 12" dia., bears S.80°W., 40 lks. dist. mkd. ¼ S 24 BT. Hemlock 24" dia., bears N.73°30'W., 49 lks. dist. mkd. ¼ S24 BT.</p>
<p>Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - June 23, 1971 - M 44-33</p> <p>-----</p> <p>A.P. Corner Section 24, T22-12 (Orig. ¼ cor. 24 by Whipple, 1893) Set OSBF I.P. with 3" bronze cap, 52" in ground on South edge of Schofield Ridge Road. 4"x4"x72" White painted cedar post S.21 3/4°W., 27.5 ft. with yellow metal location poster.</p>
<p>Fd. OK, May 1991 - M 112-29</p>
<p>1</p>