

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 5 Page(s) 1865)

Marked a Fir stub 20 ft. high 16" dia. for the cor. to secs. 18 and 19, from which
A Fir 12" dia., bears N.60°W., 24 lks. dist.
A Willow 6" dia., bears S.2°W., 22 lks. dist.
A Cherry 5" dia., bears N.5°E., 24 lks. dist.
A Fir 10" dia., bears S.85°E., 45 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1873)

The cor. to Secs. 18 and 19, which is a Fir stub, 20 ft. high and 16" dia., marked T22S R11W on E.; S18 on N.; and S19 on S. sides, with 3 notches on N. and S. sides, from which
A Fir 16" dia., bears N.60°W., 24 lks. dist. mkd. T22S R12W S13 BT.
A Willow 6" dia., bears S.2°W., 22 lks. dist. mkd. T22S R12W S24 BT.
A Cherry 8" dia., bears N.5°E., 24 lks. dist. mkd. T22S R11W S18 BT.
A Fir 20" dia., bears S.85°E., 45 lks. dist. mkd. T22S R11W S19 BT.

GL0 survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 1979-80) (duplicate of pages 2106-07)

Intersect the old decayed stump of closing cor. of secs. 18 and 19 with old bearing trees. The stump has fallen to the ground and the marks are no longer visible on witness trees. I destroy all trace of this old cor. and reestablish at the same point as follows:
Set a sandstone 20x10x8 ins., 15" in the ground for closing cor. of secs. 18 and 19, marked CC on E.; with 3 grooves on N. and S. faces, from which
A Hemlock 12" dia., bears N.72°E., 7 lks. dist. mkd. T22S R11W S18 BT.
A Hemlock 36" dia., bears S.79°E., 45 lks. dist. mkd. T22S R11W S19 BT.

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 and 19 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Driver; Schulsen and Hollingsworth - May 24, 1960 - C.S. File 42/403-14

Original 16" x 20 ft. Fir stub, missing, from which a:
12" Fir bears N.60°W., 24 lks.; now 50", evidence of orig. face showing in bark.
6" Willow bears S.2°W., 22 lks.; missing.
5" Cherry bears N.5°E., 24 lks.; missing.
10" Fir bears S.85°E., 45 lks.; now 42", face grown over.

Restoration by Slang, 1910:
Sandstone 20x10x8 ins. found badly weathered with 3 notches on N. and S. sides, from which a:
12" Hemlock bears N.72°E., 7 lks.; now 14" Fir scribe S visible.
36" Hemlock bears S.79°E., 45 lks.; now 42" Fir, face grown over.

Restored:
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd: "Ore. St. Bd. of Forestry T22S R11W R12W S18 S19 S19 S24 1960 RS 359", 30" in ground with orig. stone along N. edge of pipe, from which
23" Fir bears S.9°E., 11.5 ft. scribed T22S R11W S19 BT.
31" Fir bears N.88°W., 10.5 ft. scribed T22S R12W S24 BT.
10" Spruce bears N.75°E., 19.9 ft. scribed T22S R11W S18 BT.
42" orig. Fir BT bears S.85°E., 29.7 ft. scribed BT.
50" orig. Fir N.60°W., 15.8 ft. scribed BT RS359.

Survey by Lloyd D. Smith, LS #1101 - For: State of Oregon Dept. of Forestry - May 1991 - M 112-29

Found - OSBF 3" bronze cap dated 1960 on 1½" x 36" galv. I.P. and stone on North edge.
12" Fir, orig., N.60°W., 24 lks., now 47" x 10 ft. high stump, face partially closed and burnt, some scribes visible, in place. U.S. Plywood tag.
50" Fir, orig., N.60°W., 15.8 ft., now N.46°W., 14.3 ft., 47" x 10 ft. high stump, face partially closed and burnt. U.S. Plywood tag.
12" Hemlock, 1910, N.72°E., 7 lks., now uprooted stump, axe work visible.
23" Fir, 1960, S.9°E., 11.5 ft., now 31" face closed in place. U.S. Plywood tag.
31" Fir, 1960, N.88°W., 10.5 ft., now 36" x 3 ft. high stump, face closed, in place. U.S. Plywood tag.

New Accessories: (Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5" Fir BT, N.64°E., 14.9 ft. scribed "T22S R11W S18 BT", and bearing tree tag.
Orange carsonite marker N.33°E., 6.3 ft. to base.
Orange carsonite marker S.70°E., 4.9 ft. to base.
White painted 4 x 4 cedar post, S.85°W., 2.2 ft.