

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 315, dated Jan. 24, 1879 - (DCSO records Vol. 5 Page(s) 1864-65)

Set a Chittenwood post 4" dia., 40" long, 20" in ground for the ¼ sec. cor. on W. bdy. of Sec. 18, from which
An Alder 10" dia., bears N.70°E., 36 lks. dist.
A Chittenwood 10" dia., bears S.30°W., 36 lks. dist.

Survey by Robert B. Ward, Jr. - For: Champion International Corp. - Feb. 24, 1977 - C.S. File 58/139 and M 65-4

Set 3/4" x 36" galv. I.P. with brass cap.
BTs - 24" Hemlock, S.28°00'W., 36.8 ft.
10" Fir S.58°00'E., 44.0 ft.

Rob Ward - Sept. 24, 2001 - C.S. File 65/37-23

Found - 3" brass cap on 1" galvanized iron pipe.
Rec. 24" Hem. S.28°W., 36.8 ft. found down.
14" D.Fir stump S.58°E., 44.0 ft. healed face.
New - 18" Hem. bears N.3½°W., 26.3 ft. blazed, scribed "X
BT"
18" Hem. bears N.84°E., 43.1 ft. blazed, scribed "X
BT"
Note - All bearing trees have a red painted band & face plus yellow BT tag. 5½' gal. steel post adjacent to corner.