

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100534

PRIMARY CORNER DESCRIPTION Sec. cor. for 12 & 13 only, T22-12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Charles A. Slang, Deputy Surveyor under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2103-04)

At point for cor. of secs. 12 and 13, I set a Chittim post, 3 ft. long, 10" sq., 24" in the ground for cor. of secs. 12 and 13, marked T22S S13 on SW.; and R12W S12 on NW. faces, with 2 notches on N. and 4 notches on S. edge, from which
A Chittim 18" dia., bears S.17°30'W., 56 lks. dist. mkd. T22S R12W S13 BT.
An Alder 36" dia., bears N.77°30'W., 56 lks. dist. mkd. T22S R12W S12 BT.

Survey by Robert B. Ward - For: Champion International Corp. Feb. 24, 1977 - C.S. File 58/139 and M 65-4

Set 3/4" x 36" galv. I.P. with brass cap.
BTs - 12" Alder S.51°30'E., 35.1 ft.
12" Alder S.53°30'W., 21.5 ft.
10" Alder N.51°30'W., 38.9 ft.

Brent Bacon - For: Menasha Forest Products - 2/2005 - M147-32

Found - 3/4" iron pipe with 3" brass cap mkd: "T22S R12W R11W S12 S7 S13 1977 PLS1091"
22" Alder S.53°30'W., 20.9' healed face (record 21.5')
20" Alder, N.51°30'W., 38.4' healed face (record 38.9')
Alder to SE is uprooted.