

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 12 only, T22-12

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

| |
|---|
| <p>GLO survey by Harvey Gordon, Deputy Surveyor under Contract #52 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1853)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Hemlock 24" dia., bears S.80°W., 26 lks. dist. A Fir 24" dia., bears S.4°E., 71 lks. dist.</p> |
| <p>GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1957)</p> <p>-----</p> <p>The post and SW. bearing tree being gone, I reestablish the cor. as follows: Set a stone 12x10x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which A Fir stump 28" dia., bears S.4°E., 71 lks. dist. mkd. ¼ S BT. The other bearing tree being gone. A Hemlock 40" dia., bears N.41°W., 44 lks. dist. which I mark ¼ S BT. (1/4 Cor. 11.02 chs. So. of CC cor. for secs. 6 & 7, T22-11)</p> |
| <p>Survey by Warren D. Hootman - For: International Paper Co. - June 21, 1962 - RM 1-31</p> <p>-----</p> <p>Pipe and original BTs.</p> |
| <p>Fd. 1/2" I.Pipe, June 1971 by James Byron, DCSO - M 42-27</p> |
| <p>Fd. OK, Jan. 1981 by R. Hintz - M 86-60</p> |
| <p>B.L.M. Resurvey by Deborah M. Stephens and Harvey E. Wofford dated April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19632)</p> <p>-----</p> <p>Found - 1" iron rod, loosely set, projecting 4 ins. above ground, from which the remains of an original bearing tree:</p> <p>A fir stump, 30 ins. diam., bears S.20½°E., 73 lks. dist., with a healed blaze. (Record S. 4°E., 71 lks.)</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: right;">T22S R12W R11W 1/4 S 12 1991</p> <p>(Cont. Next Page)</p> |

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100574

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 12 only, T 22-12

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |

from which a new bearing tree

An alder, 4 ins. diam., bears S. 57½° W., 22½ lks.
dist., mkd. 1/4 S12 BT.

(Cont. Next Page)

No other suitable accessories available.

Deposit the iron rod inside and a white "DEEP-1" magnetic
marker at base of the stainless steel post.