

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W 1/4 Cor Section 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - For: Douglas County - July 9, 1971 - C.S. File 56/5-16 and M 42-27

This corner set by survey & lies in bottom of ravine runs N-S
Set brass cap at cor. mkd: County Surveyors Office

R	T 22 S	R
12	$\frac{1}{4}$ S 6	11
W	4	W

1971

BT - 80" Cedar, S.80°W., 63.4 ft. scribed $\frac{1}{4}$ S6 CS BT.
No other trees available.

Fd. OK, Jan. 1981 by R. Hintz - M 86-60

B.L.M. Resurvey by Deborah M. Stephens and Harvey E. Wofford dated April 1990 thru April 1995 under group #1521. (DCS0 records Vol. 51 Page(s) 19634)

The 1/4 sec. cor. of sec. 6 only, T.22 S., R.11 W., established by Byron in 1971, and accepted by Hoesly in 1977 and Hintz in 1981, and is accepted as the corner, determined from the remains of a bearing tree mkd. by Byron:

A cedar stump, 80" diam., bears S.80°W., 96 lks. with scribe marks visible on open blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

	T22S	
R12W		R11W
		1/4 S 6
		1991

from which a new accessory

A stainless steel post, 28" long, 2½" diam., set 24" in the ground, for a reference monument, bears N.36°30'00"E., 0.355 chs., with brass cap mkd. T22S R11W S6 RM 1991 and an arrow pointing to the corner.

No other suitable accessories available.

Deposit a white "DEEP-1" magnetic marker at base of cor post.
The corner is located in a ravine, drains N.

Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCS0 rec Vol. 53 Pgs 20241-2)

Fd OK by Brent Bacon, 3/2005 - M147-44