

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100672

PRIMARY CORNER DESCRIPTION Ref. mon. on rg. line (W bdy Sec. 6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - For: Douglas County - June 10, 1971 - C.S. File 56/5-12 and M 42-27

(Reference monument #1 on Range line Sec. 6, T22-11 and Sec. 1 T22-12)

Set brass cap on Range line marked:

Douglas County Surveyor Office

| | | |
|----|-----------|----|
| R | T 22 S | R |
| 12 | R M #1 | 11 |
| W | S 1 S 6 | W |
| | 1971 | |

Bearing Objects:

5/8" Iron rod, N.1°E., 47.4 ft. This rod on N. edge of highway.

3" + , S.84°W., 11.4 ft. This cross about 4 ft. above ground on high rock bluff.

Corner 217.37 ft. North of ¼ corner to Sec. 1 only.

Fd. and used by OSHD, June 1987 - DCSO files 0-1

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Jan. 18, 1990 - C.S. File 64/5-9

Monument gone. Apparently dug out.

Found - A 3" + marked in high rock bluff approx. 4 ft. above ground, bears S.55°E., 17.9 ft.

5/8" I.R. and SW "cross" from 1971, not found.

Set a 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. x 32" long I.P. at a point N.55°W., 17.9 ft. from previously described + in rock bluff. BC/IP protrudes 14" above ground, is surrounded by a 2½ ft. dia. mound of sandstone. Cap stamped: Douglas County Surveyors T22S RM 1 R12W S1 S6 R11W RESET 1990.

New Accessories:

5/8" x 30" long I.R. with DCSO alum. cap stamped "B0 1" protrudes 3" above ground under East guard rail, bears N.24½°E., 51.4 ft.

A 5" + marked in high rock bluff approx. 4½ ft. above ground, bears S.72°W., 10.0 ft.

DCSO drill cap stamped "T22S RM2 R12W S1 S6 R11W 1990", bears N.68½°W., 111.7 ft. RM 2 drill cap set 6" below ground in sandstone. Two boat spikes are set over drill cap for future magnetic detection.

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100672

PRIMARY CORNER DESCRIPTION Ref mon on Rg line W bdy S 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Following new accessories are for RM 2 only:
A found 6" + on high rock bluff approx. 5 ft. above drill cap, bears S.84°W., 11.4 ft.
Marked a 6" + on high rock bluff approx. 5 ft. above drill cap, bears S.10°E., 11.4 ft.
A DCSO BC/IP marked "T22S RM1 R12W R11W S1 S6 RESET 1990", bears S.68½°E., 111.7 ft.

BLM resurvey dated April 1990 thru April 1995, under group #1521 Vol. 51 Pg. 19636

A point established on the section line by Byron in 1971 and perpetuated by the Douglas County Surveyor's Office in 1990, now serves as an angle point on the section line; monumented with an iron post, 1½" diam., firmly set in a mound of stone, 2 ft. base, projecting 4" above the mound of stone, with brass cap mkd.
DOUGLAS COUNTY SURVEYOR
T22S
R 12 | S 1 | S 6 | R 11
W | | W
RESET
1990
from which a bearing object mkd. by Byron
A rock face of a highway cut bears S.55°E. 27 lks. mkd. X. and a bearing object and reference monument mkd. by the County Surveyor's Office
A rock face of highway cut, bears S.72°W., 15 lks. mkd. X.
A brass tablet, 2½" diam., firmly set flush in solid rock, bears N.68½°W., 169 lks., with top mkd. T22S RM2 R12 S1 S6 R11W 1990.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20215)

An angle point bet. secs. 1 & 6, monumented with an iron post, 1½" diam., firmly set, and in a mound of stone, 2 ft. base, to top, w/brass cap mkd. DOUGLAS COUNTY SURVEYORS
T22S
R 12 | S 1 | S 6 | R 11
W | | W
RESET
1990
continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100672

PRIMARY CORNER DESCRIPTION Ref. mon. on rg. line (W bdy Sec 6)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

from which a bearing object mkd. by Byron, reported by Stephens and Wofford

A rock face of highway cut, bears S.55°E., 27 lks., mkd. with an X.

and a bearing object and reference monument set by Ingram, reported by Stephens and Wofford

A rock face of highway cut, bears S.72°W., 15 lks., mkd. with an X.

A brass tablet, 2½" diam., firmly set flush in solid rock, bears N.68½°W., 169 lks., with top mkd. T22S RM2 R12 S1 S6 R11W 1990.