

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 100676

PRIMARY CORNER DESCRIPTION Meander Cor. on left bank Umpqua River

Alias 834010 Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Harvey Gordon, Deputy Surveyor, under contract No. 69, dated Feb. 2 1857. (DCSO records Vol. 5 Page(s) 1853)

Left bank of Umpqua River.

Set post, from which

A Fir, 18" dia., bears S.55°W., 17 lks. dist.

A Cherry, 6" dia., bears S.60°E., 55 lks. dist.

BLM resurvey dated April 1990 thru April 1995, under group #1521 (DCSO records Vol. 51 Page(s) 19637)

Point for the meander cor. of secs. 1 and 6 on the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 24 ins. in the ground, with brass cap mkd.

MC

S 1 | S 6
R12W | R11W
T22S
1991

No suitable accessories available.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20215)