

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 104100

PRIMARY CORNER DESCRIPTION NW Cor. S. 6, T23-11 (NE cor. S. 1, T23-12)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under Contract #341, dated 1880 - (DCSO records, C.S. File 62/35-15B)

-----  
Set post cor. to Twps. 22 & 23.S of R. 11 & 12, from which  
A Maple 20" dia., bears N .67°W., 50 lks. dist.  
A Maple 10" dia., bears N.82°E., 40 lks. dist.  
No other trees convenient to mark.

GLO survey by William Hall, Deputy Surveyor, under Contract #471, dated April 26, 1883 - (DCSO records Vol. 5 Page(s) 1870)

-----  
Began this survey at the cor. of Ts. 22 & 23 S., of Rs. 11 and 12 W., which is a post 2½ ft. above ground, 4" sq., mkd. T22S R11W S31 on NE.; S6 on SE.; T23S R12W S1 on SW.; S36 on NW. faces, from which  
A Maple 20" dia., bears N.67°W., 50 lks. dist. mkd. T22S R12W S36 BT.  
A Maple 10" dia., bears N.82°E., 40 lks. dist. mkd. T22S R11W S31 BT.  
No other trees found.

Survey by Clifford Stephens - For: Jacobson Bros. - 1952 - C.S. File 58/37

-----  
I find 1/2" Iron rod projecting 26" above the ground with 6 notches on 3 sides of rod. I concluded that this rod had been in this location for a good number of years by the rust and moss accumulated on said rod. No original BTs found. This hillside showed signs of many fires. (I check the location of the corner by chaining East) From the evidence on the ground, I accept this as being the location of the original corner. I now establish a new BT from the 1/2" Iron rod:  
A Fir 8" dia., bears S.81°E., 39.6 ft.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Nov. 1958 - C.S. File 42/403-1

-----  
Original Post, now missing. 1/2" Iron rod set in place by Elliott State Forest Survey, from which a:  
20" Maple bears N.67°W., 50 lks.; now missing, Clump in place.  
10" Maple bears N.82°E., 40 lks.; now 15", chopped out by unknown party, no scribe visible.  
(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 104100

PRIMARY CORNER DESCRIPTION NW cor. S 6, T23-11; NE S1, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Closing township corner bears West 480 lks.; in place.  
8" Fir bears S.81°E., 39.6 ft.; now 13", scribed BT S6T2  
R11 visible. (Stephens 1952 BT)  
Set 1½" x 36" galv. Iron pipe with 3" bronze cap mkd. "Oregon  
State Board of Forestry T22S R11W S31 T23S R11W R12W S1 S6  
1958 RS 359", 33" in ground over 1/2" Iron rod, and from  
which a:  
17" Myrtle, in clump, bears S.24°W., 58.6 ft., bark  
scribed T23S R12W S1 BT.  
28" Fir bears N.49°E., 67.6 ft. scribed RS 359.  
Set 4x4x72" white painted cedar post, 1.0 ft. NW of pipe.  
OSBF metal location poster on 8" Fir BT.

Survey by Harvey Wilcox - For: International Paper - Feb.  
1992 - M 114-75 and C.S. File 63/119  
-----  
Found - 3" brass cap on 2" O.D. Iron pipe with 4"x4" white  
post alongside. (Gibson)  
26" Fir with healed face and tag bears S.83°E., 47.0  
ft. (39.6 ft. Stephens)  
30" Fir snag with visible scribe bears N.49°E., 68.0  
ft. (Gibson)  
New BT - 10" Maple scribed "T23SR12W S1 BT" with "X" and  
tags, bears S.64°W., 22.4 ft.