

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 5 Page(s) 1865)

Marked a Fir 6" dia., for the ¼ sec. cor. bet. secs. 18 and 19, from which
 An Alder 14" dia., bears S.45°E., 24 lks. dist.
 An Alder 14" dia., bears N.55°W., 19 lks. dist.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - witnessed by Steenson and Poitras - Sept. 1961 - C.S. File 42/403-22

No evidence of original corner found.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore.St. Bd. of Forestry ¼ S18 S19 1961 RS 359", 32" in ground and from which a
 18" Hemlock bears S.25°E., 16.3 ft. scribed ¼ S19 bT RS359
 26" Hemlock bears N.67°E., 40.5 ft. scribed ¼ S18 BT.
 OSBF metal location poster on 4" hemlock S.11°E., 6.4 ft.
 Set 4"x4"x72" white painted cedar post 1 ft. SE of pipe.

Survey by Lloyd D. Smith - For: Oregon State Board of Forestry - May 1, 1991 - M 112-29

Found - OSBF 3" bronze cap dated 1961 on 1½" x 36" galv. I.P. in place.
 18" Hemlock S.25°E., 16.3 ft., now 21" x 4 ft. high rotted stump, scribes visible, in place.
 26" Hemlock N.67°E., 40.5 ft., now rotted windfall.
 White painted cedar post SE 1.0 ft. in place.
New Accessories:
 22" Hemlock N.36°E., 28.2 ft. scribed "¼ S18 BT" and bearing tree tag.
 20" Hemlock N.31°W., 55.8 ft. scribed "¼ S18 BT" and bearing tree tag.
 15" Hemlock S.56°E., 20.7 ft. scribed "¼ S19 BT" and bearing tree tag.
 12" Hemlock S.34°W., 13.9 ft. scribed "¼ S19 BT" and bearing tree tag.