

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Pg 1956)

Set a post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
A Myrtle 24" dia., bears N.62°W., 27 lks. mkd. ¼ S BT.
A Fir 40" dia., bears South, 7 lks. dist. mkd. ¼ S BT.

Survey by S.O. and H.J. Newhouse - For: Cape Arago Lumber Co. March 1957 - C.S. File 42/256 and M 1-54

Set an Iron pipe and post, from which the orig. BTs:
24" Myrtle now 36", 17.8 ft. Remark ¼ S6 BT.
40" Fir now 48", 4.6 ft. Chopped out, scribing visible.

Survey by Wilford N. Haines - July 20, 1960 - C.S. File 51/109-1

I find Iron pipe. Fir BT, now a stump. Myrtle BT gone.
I drive a 1" x 1" x 48" T. Iron 24" in ground by pipe.
No new bearing trees.

Fd. OK, Jan. 1981 by R. Hintz - M 86-60

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO rec Vol. 53 Pgs 20238-9)

From the ¼ sec. cor. of secs. 6 & 7, remonumented by Newhouse, in 1957, utilized by Hootman, in 1959, Haines, in 1960, also utilized by Hintz, in 1981; monumented with an iron pipe, 3/4" diam., firmly set, projecting 4" above ground (alongside of which the T-shaped iron bar set by Haines, 1" x 1", firmly set, projecting 6" above ground, with brass washer mkd. WILFORD N. HAINES LS 239 SURVEY POINT DRAIN OR), from which the remains of an original bearing tree:

A fir stump, 49" diam., bears S.2°E., 8½ lks., no marks visible. (Record, South, 7 lks.)

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T22S R11W

¼ $\frac{S}{S} \frac{6}{7}$

1992

No suitable accessories available.

Deposit 3/4" iron pipe and white "DEEP-1" magnetic marker at base of stainless steel post and set T-iron alongside.

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Brent Bacon - For: Menasha Forest Products - 2/2005 - M147-32

Found - 2½" pipe with ¾" BLM brass cap marked "T22S R11W ¼ S6 S7 1992", next to T-shaped rod with washer.

49" fir stump, S.2°E., 5.9'

New BTs- 7" fir, N.7°E., 14.0', scribed "¼ S6 BT"

9" fir, S.83°E., 6.6', scribed "¼ S7 BT"

10" fir, S.69°W., 17.8', scribed "¼ S7 BT"