

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 5 Page(s) 1868-69)

Marked a Vine Maple 5" dia. for the ¼ sec. cor. bet. secs. 19 and 20, from which
 A Fir 30" dia., bears S.30°E., 48 lks. dist.
 A Fir 30" dia., bears S.8°W., 39 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1963)

Unable to find the old ¼ sec. cor. bet. secs. 19 and 20. Set a stone 14x10x5 ins., 10" in the ground, marked ¼ on W. face, from which
 An Alder 14" dia., bears N.10°E., 14 lks. dist. mkd. ¼ S BT.
 An Alder 24" dia., bears N.5°W., 29 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: D. Steenson and E. Poitras - Sept. 15, 1961 -C.S. File 42/403-21

Original 1894 stone, 14"x10"x5", now missing, from which a:
 14" Alder bears N.10°E., 14 lks.; now rotten stub 2 ft. high.
 24" Alder bears N.5°W., 29 lks.; now 30" stub 6 ft. high, evidence of old face in bark and in rotted wood.
 Stream bears South 200 lks.; in place, - 1894 line blazes bear North 100 lks.
Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd. "Oregon State Board of Forestry ¼ S19 S20 1961 RS 359", 33" in ground, in mound of stone, and from which a
 20" Cedar bears N.49°W., 23.9 ft. scribed ¼ S19 BT RS 359.
 24" Cedar bears N.82°E., 63.9 ft. scribed ¼ S20 BT.
Set 4"x4"x72" white painted cedar post 1 ft. NE of pipe.

Survey by Lloyd D. Smith - For: Oregon State Board of Forestry - May 1, 1991 - M 112-29

Found - OSBF 3" bronze cap dated 1961 on 1½" x 36" I.P., in place.
 24" Cedar N.82°E., 63.9 ft., now 32" x 4 ft. high stump, in place with bearing tree tag.
(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories:

7" Fir N.4°E., 33.2 ft. scribed "¼ S20 BT" w/BT tag.

10" Fir N.70°E., 57.8 ft. scribed "¼ S20 BT" w/BT tag.

5" Fir S.79°W., 1.5 ft. scribed "¼ S19 BT" w/BT tag.

Orange carsonite marker S.29°W., 5.7 ft. to base.

White painted 4 x 4 cedar post S.29°W., 5.7 ft.

1 ft. wide creek North 1.0 ft. course SE.