

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 5 Page(s) 1866-67)

Marked Fir stub 24 ft. high, 30" dia. for the ¼ sec. cor. between secs. 17 and 18, from which
A Cedar stub 40 ft. high 30" dia., bears S.10°E., 50 lks.
A Fir stub 60 ft. high 16" dia., bears S.80°W., 30 lks.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1972)

I could find no trace of ¼ sec. cor. it having evidently been destroyed by forest fires.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Aug. 1, 1973 - M 51-28

Set OSBF I.P. with 3" bronze cap 33" in ground, from which
66" Fir N.38°E., 104.5 ft. "RS 359" with yellow metal location poster.
4'x6' sandstone, S.38°W., 17.7 ft. 9" X BO.
White painted cedar post N.55°E., 3.5 ft.

Survey by Lloyd D. Smith - For: Oregon State Board of Forestry - Aug. 1989 - M 108-58

Found - 1972 OSBF pipe with cap.
66" Fir N.38°E., 104.5 ft., now 60" x 2 ft. high rotted stump in place, face closed, RR spike in top center of stump, with yellow metal location poster.
4 ft. x 6 ft. high sandstone face, S.38°W., 17.7 ft. to 9" "XBO", in place.
New Accessories:
Orange carsonite boundary marker, DBM-250R, S.50°E., 4.7 ft. to base.
Orange carsonite boundary marker, CBM-2500, N.32°W., 2.7 ft. to base.
White painted cedar post, N.69°E., 3.1 ft.

Jerry Estabrook - For: Moore Mill & Lumber Co. - 7/2020 - M177-34

Found - A 1½" iron pipe with 3" brass cap per M51-28.
A 66" Fir with healed face and tag bears N.38°E., 104.5'.
Continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 4'x6' high sandstone face marked "XB0" bears
S.38°W., 17.7'
An orange carsonite post bears S.50°E., 4.7'.
An orange carsonite post bears N.32°W., 2.7'.
New BO - A Steel post bears N.28°E., 2.6'.