

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Wm. R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Pg 1958)</p> <p>-----</p> <p>A Cherry 12" dia., which I marked ¼ S. on W. side for ¼ sec. cor., from which</p> <p>    A Fir 30" dia., bears N.5°E., 62 lks. mkd. ¼ S BT.</p> <p>    A Cherry 10" dia., bears S.45°W., 14 lks. mkd. ¼ S BT.</p>
<p>Elliott State Forest Boundary Survey - L. Beyers and E. Lough 1939 or 1941 ? - (DCSO Field Book 123 Page 14)</p> <p>-----</p> <p>Found ¼ corner Cherry tree 18", from which</p> <p>    A Fir 4 ft. dia., bears N.5°E., 40 ft. dist.</p> <p>    A Myrtle 30" dia., bears N.20°E., 15 ft. dist.</p>
<p>Survey by S.O. and H.J. Newhouse - For: Cape Arago Lumber Co. March 1957 - C.S. File 42/256 and M 1054</p> <p>-----</p> <p>The 12" Cherry corner tree is gone.</p> <p>Identify corner from the original BTs:</p> <p>    30" Fir, now 54", N.5°E., 41.0 ft.</p> <p>    10" Cherry, now rotten stump, S.45°W., 9.2 ft.</p> <p>We drive an Iron pipe, from which</p> <p>    10" Myrtle N.29°W., 14.5 ft. scribed ¼ S7 BT.</p> <p>    54" Fir N.5°E., 41.0 ft. scribed bark, ¼ S8 BT.</p> <p>In place of a post, we mark a 72" Myrtle, North 6.5 ft. ¼ corner.</p>
<p>Fd. OK, June 1962 by W. Hootman - RM 1-31</p>
<p>Gary T.Smither for Scott Timber Co. Jan. - April 1997 - M 124-51</p> <p>-----</p> <p>Found - 3/4" inside dia. iron pipe set by Newhouse in 1957.</p> <p>    48" original D.Fir sawed stump, we open face and expose original "4 S" of scribe. Set spike and tag on top of stump. Bears N.5°E., 41.0 ft. to spike.</p> <p>    No other BT's remain.</p> <p>New Bearing Trees -</p> <p>    75" D.Fir, S.40°W., 53.1 ft. to spike side center, bark scribed "¼ S7 BT"</p> <p>    14" Alder, N.55°W., 7.8 ft. to spike side center, bark scribed "¼ S7 BT"</p> <p>    11" Alder, N.52°E., 21.4 ft. to spike side center, bark scribed "¼ S8 BT"</p> <p>Note - Set 6 ft. steel post near monument.</p>
<p>continued next page</p>

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Brent Bacon - For: Menasha Forest Products - 2/2005 - M147-32  
-----

Found - 3/4" iron pipe  
48" fir stump, N.5°E., 40.0' to face, visible scribe  
"4S"  
14" alder, N.52°E., 21.4' to spike visible bark  
scribe "¼ S8 BT"  
76" fir, S.38°W., 52.9' to spike visible bark scribe  
"¼ S7 BT"  
17" alder, N.52°W., 7.8' to spike visible bark  
scribe "¼ S7 BT" (record N.55°W)  
Metal fence post, south 1.0'