

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1953)

Set a post 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. mkd. ¼ S. on W. face, from which
A Fir 30" dia., bears N.2°W., 116 lks. dist. mkd. ¼ S BT.
A Maple 20" dia., bears N.36°E., 9 lks. dist. mkd. ¼ S BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough 1939 or 1941 ? - (DCSO Field Book 123 Page 18)

Found ¼ corner bearing trees. Replaced post, from which
A Fir 4 ft. dia., bears N.2°W., 76 ft.
A Maple 2 ft. dia., N.36°E., 6 ft.

Survey by Richard J. Hintz LS #497 - For: International Paper Co. - May 1980 - M 83-57

Found - Orig. 30" Fir now a stump, bears N.2°W., 76.6 ft., opened face plainly visible.
Orig. Maple bears N.15°E., 8 ft. No definite point to take a bearing and distance to.
Set 1¼" Iron pipe with stamped brass cap.

Fd. OK, Jan. 1981 by R. Hintz - M 86-60

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO rec Vol. 53 Pgs 20225-6)

From the ¼ sec. cor. of secs. 5 & 6, remonumented by Hintz, in 1980, utilized by Hintz in 1983; monumented with an iron post, 2" diam., firmly set, projecting 4" above ground, with brass cap mkd.

T22S PLS 497 R11W

1/4

S 6 S 5

1980

from which the remains of original bearing trees

A maple, 33" diam., bears N.15°E., 12 lks., no marks visible. (Record, N.36°E., 9 lks.)

A fir stump, 48" diam., bears N.2°W., 116 lks., no marks visible on open blaze.

and a new bearing tree

A fir, 10" diam., bears S.49°W., 71½ lks., mkd. ¼ S6 BT.